

Rescue Equipment

New for 2009



BCT 4120 Even Quieter



Features:

- even quieter
- smoother operation
- lighted handle
- new optimized micro pump design

Battery Operated Combi Tool 4120

max. spreading travel	10½" (268 mm)
spreading force (at back of tips)	11,690 lbf (52 kN)
cutting force (in notch)	49,000 lbf (218 kN)
cutting force (blade center)	18,660 lbf (82 kN)
pulling force	6,600 lbf (29.3 kN)
pulling distance	12 7/8" (327 mm)
dimensions (L x W x H)	28" x 12" x 9" (712 x 305 x 230 mm)
weight ready for use	34 lbs (15.4 kg)

4240 Spreader Smaller, But Stronger



Features:

- Holmatro's most powerful 27" spreader
- larger serrated tips for better grip and reduced tearing
- UL Listed
- UL Classified to NFPA1936

4240 Spreader

operating pressure	10,500 psi (720 bar)
max. spreading force (at back of tips)	33,625 lbf (150 kN)
max. spreading force (HSF)	13,184 lbf (59 kN)
max. spreading force (LSF)	8,476 lbf (38 kN)
max. spreading travel	27 3/8" (695 mm)
dimensions (L x W x H) (twin-line)	33 1/16" x 11 11/16" 8 1/8" (840 x 297 x 206 mm)
weight ready for use (twin-line)	44.5 lbs (20.2 kg)
dimensions (L x W x H) (CORE)	33 1/16" x 11 11/16" 8 1/8" (771 x 297 x 206 mm)
weight ready for use (CORE)	41.5 lbs (18.8 kg)

4055 NCT Larger & Stronger for Today's NCT



ALSO CLASSIFIED IN ACCORDANCE WITH NFPA 1936, Standard on Powered Rescue Tools, 2005 Edition



Features:

- wider blade opening to deal with larger roof pillars
- deeper reach
- highest cutting force of any Holmatro cutter
- UL Listed
- UL Classified to NFPA1936

4055 NCT	
cutting force	228,855 lbf (1018 kN)
blade opening	8 5/8" (219 mm)
cutting capacity (NFPA)	A8 B7 C7 D8 E8
weight ready for use (twin-line)	45 lbs (20.4 kg)
dimensions (L x W x H) (twin-line)	35 1/4" x 10 3/8" x 7 5/8" (895 x 264 x 194 mm)
weight ready for use (CORE)	43 lbs (19.5kg)
dimensions (L x W x H) (CORE)	32 1/2" x 10 3/8" x 7 5/8" (825 x 264 x 194 mm)

SMC 4006 Save Your Blades



Features:

- adjustable handle
- compact
- add to existing Holmatro systems
- designed to cut hardened round materials



SMC 4006	
blade opening	1" (25.4 mm)
cutting force	43,500 lbf (193.5 kN)
round bar	3/4" (20 mm)
weight ready for use (twin-line)	16.8 lbs (7.6 kg)
dimensions (L x W x H) (twin-line)	18" x 4 1/2" x 9 1/4" (389 x 114 x 234 mm)
weight ready for use (CORE)	14.5 lbs (6.5 kg)
dimensions (L x W x H) (CORE)	15 3/8" x 4 1/2" x 9 1/4" (389 x 114 x 234 mm)
handle	adjustable rotating



Holmatro N.V.
World Headquarters
Raamsdonksveer, The Netherlands



Holmatro, Inc.
Manufacturing, Sales & Service
505 McCormick Drive
Glen Burnie, MD 21061
tel: 410-768-9662
fax: 410-768-4878



Holmatro Rescue Equipment B.V.
Raamsdonksveer, The Netherlands



Holmatro China
Shanghai, China
Sales & Service



Holmatro Polska Sp. z o.o.
Warsaw, Poland
Manufacturing, Sales & Service

www.holmatro-usa.com